

# Series 3 400

## LMS by Dulas Life Sciences

Reliable and accurate temperature control.

Our cooled incubators offer optimum temperature control from -10°C to +50°C with an average variation of 0.5°C and fluctuation of 0.1°C, or 0°C to +60°C upon request.

LMS has been producing scientific incubation products since 1979.



## Key Features



### Door lock

Preventing unauthorised access



### Defrost

Automatic, with a manual override built in



### Fruit fly modification

Prevents corrosion caused by fruit flies



### Self-evaporating drip tray

For additional temperature probes



### Fan assisted air circulation

Keeping temperatures consistent



### Heating / Cooling control

Optimising power usage when needed

# Cooled Incubator - Stainless Steel Interior And White Exterior

Series 3		
Standard	Model	400
	RJ45 interface for remote access (wired)	Yes
	Capacity (L)	450
	Material	Stove enameled mild steel
	Chamber material	Stainless steel
	Temperature range	-10°C to +50°C
	Accuracy	+0.5°C
	Height exterior (mm)	1810
	Width exterior (mm)	690
	Depth exterior (mm)	920
	Shelf size (mm)	510 x 600
	Weight (kg)	140
	Number of shelves	3
	Fruit fly modification	Yes
	Access porthole	Yes
	Programmable controller	Yes
	Dual temperature control	Yes
Optional extras	Double glazed door*	Yes
	Inner perspex door	Yes
	Extra shelves	Yes
	Fully programmable interior illumination	Yes
	Independent 24 hour / 7 day timer	Yes
	High / low AV alarm	Yes
	Integral chart recorder	Yes
	Internal 13A socket (EU/UK)	Yes
	Drying mode	Yes
	Corrosive conditions evaporator	Yes
	Pre-programming service	Yes